

MATERIAL SAFETY DATA SHEET

PILGRIM PERMOCOAT, INC.
402 S. 22ND ST.
TAMPA, FLORIDA 33605

PILGRIM CODE-ANT
ISSUE DATE-11/16/87
REVISED-1/15/05

A. TRADE NAME - EM 3-2,A COMPONENT

CHEMICAL NAME - EPOXY FORMULATION

FORMULA -MIXTURE

EMERGENCY CONTACT - ROBERT FORLONG

CAS# - NA

DOT CLASS - NOT REGULATED

HMIS: H-1, F-1, R-0

MOLECULAR WEIGHT - NA

DAY PHONE - 813-248-3328

NIGHT PHONE - 813-685-5282

B. FIRST AID MEASURES

EYES - IMMEDIATELY FLUSH EYES WITH PLENTY OF WATER FOR AT LEAST 15 MINUTES HOLDING LIDS APART. CALL A PHYSICIAN.

SKIN - WASH THOROUGHLY WITH SOAP AND WATER. IF IRRITATION DEVELOPS AND PERSISTS, SEE A PHYSICIAN. WASH CLOTHES BEFORE REUSE.

INHALATION - REMOVE TO FRESH AIR. IF NOT BREATHING GIVE ARTIFICIAL RESPIRATION, PREFERABLY MOUTH TO MOUTH. IF BREATHING IS DIFFICULT, GIVE OXYGEN. CALL A PHYSICIAN!

INGESTION - MAY CAUSE GASTROINTESTINAL DISTRESS, IRRITATION ULCERATION. DRINK LARGE QUANTITIES OF WATER. CONSULT A PHYSICIAN.

C. HAZARDS INFORMATION**FIRE AND EXPLOSION**

FLASH POINT - >200°F CLOSED CUP

AUTO IGNITION TEMPERATURE - NA

UNUSUAL FIRE AND EXPLOSION HAZARDS - DECOMPOSITION AND COMBUSTION PRODUCTS MAY BE TOXIC.

HEALTH

INHALATION - IRRITATION, SENSITIZATION AND DERMATITIS.

INGESTION - MAY CAUSE GASTROINTESTINAL DISTRESS OR IRRITATION.

SKIN - PROLONGED AND REPEATED CONTACT MAY CAUSE IRRITATION AND RESULT IN SENSITIZATION AND ALLERGIC REACTION.

EYES - VAPOR MAY CAUSE IRRITATION, REDNESS AND TEARING. LIQUID MAY CAUSE SEVERE IRRITATION WITH POSSIBLE IRREVERSIBLE INJURY.

UNUSUAL CHRONIC TOXICITY - NONE KNOWN.

PERMISSIBLE CONCENTRATION (AIR) - NOT KNOWN

HAZARD DATA

PRIMARY ROUTES OF EXPOSURE:

DERMAL.

ORAL LD 50:

(RAT) >5,000 MG/KG

DERMAL LD 50:

(RABBIT) >4,000 MG/KG

SKIN IRRITATION:

(RABBITS) MODERATE

D. PRECAUTIONS/PROCEDURES

VENTILATION - GOOD MECHANICAL VENTILATION AND LOCAL EXHAUST

NORMAL HANDLING - DO NOT GET IN EYES, ON SKIN OR CLOTHING. DO NOT BREATHE VAPORS. KEEP CONTAINERS CLOSED. USE WITH ADEQUATE VENTILATION. WASH THOROUGHLY AFTER HANDLING.

STORAGE - STORE INB COOL, DRY AREA AWAY FROM HEAT, STRONG OXIDIZERS. PROTECT FROM DAMAGE

SPILL OR LEAK - ABSORB SPILL ON SAND, EARTH OR VERMICULITE.

CAREFULLY COLLECT INTO CLOSED CONTAINERS FOR DISPOSAL ACCORDING TO FEDERAL, STATE OR LOCAL REGULATIONS.

FIRE EXTINGUISHING PRECAUTIONS - WEAR FULL PROTECTIVE GEAR AND NIOSH/MSHA APPROVED SELF- CONTAINED BREATHING APPARATUS.

FIRE EXTINGUISHING AGENTS TO AVOID - SOLID STREAM OF WATER OR FOAM MAY CAUSE FROTHING, SPLATTERING AND SPREAD HAZARD.

SPECIAL PRECAUTIONS/PROCEDURES - COOL CONTAINERS EXPOSED TO FLAME WITH WATER SPRAY.

E. PERSONAL PROTECTIVE EQUIPMENT

RESPIRATORY EQUIPMENT - ORGANIC CHEMICAL CARTRIGE RESPIRATOR, IF NEEDED.

EYES - CHEMICAL SPLASH - PROOF GOGGLES.

HANDS, ARMS AND BODY - RUBBER OR POLYETHYLENE GLOVES AND FULL BODY COVERING CLOTHING.

OTHER CLOTHING AND EQUIPMENT - EYE WASH FOUNTAIN AND SAFETY SHOWER.

F. PHYSICAL DATA

DESCRIPTION - DIGLYCIDYL ETHER RESIN

BOILING POINT - >200°F

VAPOR DENSITY - NA

SOLUBILITY IN WATER - NONE

EVAPORATION RATE - NIL

SPECIFIC GRAVITY - 1.1

VAPOR PRESSURE - CA. 1 MM HG AT 180C

PH - NA

% VOLATILES (BY VOLUME) - NIL

G. REACTIVITY DATA

STABILITY - STABLE

INCOMPATIBLE MATERIALS - STRONG OXIDIZERS, ACIDS AND EPOXY CURING AGENTS.

HAZARDOUS DECOMPOSITION PRODUCTS - CO, CO2, NOX AS A RESULT OF THERMAL DECOMPOSITION.

HAZARDOUS POLYMERIZATION - WILL NOT OCCUR.

H. HAZARDOUS INGREDIENTS (MIXTURES)

INGREDIENTS	PERCENTAGE	CAS#	TLV
EPOXY RESIN	>90%	25068-38-6	NE
C12 & C14 ALKYL GLYCIDYL ETHERS	<10%	686909-97-2	NE

I. ENVIRONMENTAL

BIODEGRADABILITY - NOT KNOWN
WASTE DISPOSAL METHODS - DISPOSE OF AS HAZARDOUS WASTE IN APPROVED WASTE DISPOSAL FACILITIES IN ACCORDANCE WITH FEDERAL, STATE AND LOCAL REGULATIONS.

J. REFERENCES

PERMISSIBLE CONCENTRATION REFERENCES - ACGIHTWA, TLV, AND STEL
REGULATORY STANDARDS - TITLE 49 CFR SECTION 173.118, 172.101
GENERAL - NIOSH GUIDE TO CHEMICALS

K. ADDITIONAL INFORMATION

EMPTY CONTAINER HANDLING!
 WARNING! EMPTIED CONTAINER RETAINS PRODUCT RESIDUE AND VAPORS.
 OBSERVE ALL LABEL PRECAUTIONS EVEN AFTER CONTAINER IS EMPTIED.
 DO NOT CUT, DRILL, GRIND, OR WELD ON OR NEAR CONTAINER.

INFORMATION CONTAINED HERIN IS BELIEVED TO BE ACCURATE. HOWEVER, IT IS PROVIDED SOLELY FOR THE CUSTOMERS CONSIDERATION, INVESTIGATION AND VERIFICATION. PILGRIM PERMOCOAT INC. HEREBY SPECIFICALLY DISCLAIMS ANY AND ALL WARRANTIES, EXPRESS OR IMPLIED, REGARDING THE ACCURACY AND COMPLETENESS OF SUCH INFORMATION, AND MAKES NO REPRESENTATIONS WITH RESPECT THERETO.