

MATERIAL SAFETY DATA SHEET

PILGRIM PERMOCOAT, INC.
402 S. 22ND. STREET
TAMPA, FLORIDA 33605

PILGRIM CODE-PPF
ISSUE DATE-12/16/96

A. TRADE NAME - SolvGard LV, A COMPONENT
CHEMICAL NAME - EPOXY FORMULATION

CAS# - 25068-38-6
DOT CLASS - NOT REGULATED
HMIS: H-1, F-1, R-0
MOLECULAR WEIGHT - NA

FORMULA - PROPRIETARY

EMERGENCY CONTACT -ROBERT FORLONG

DAY PHONE- (813) 248-3328
NIGHT PHONE- (813) 685-5282

B. FIRST AID MEASURES

EYES - IMMEDIATELY FLUSH EYES WITH PLENTY OF WATER FOR AT LEAST 15 MINUTES HOLDING LIDS APART. CALL A PHYSICIAN.

SKIN - WASH THOROUGHLY WITH SOAP AND WATER. IF IRRITATION DEVELOPS AND PERSISTS, SEE A PHYSICIAN. WASH CLOTHES BEFORE REUSE.

INHALATION - REMOVE TO FRESH AIR. IF NOT BREATHING GIVE ARTIFICIAL RESPIRATION, PREFERABLY MOUTH TO MOUTH. IF BREATHING IS DIFFICULT, GIVE OXYGEN. CALL A PHYSICIAN!

INGESTION - MAY CAUSE GASTROINTESTINAL DISTRESS, IRRITATION ULCERATION. DRINK LARGE QUANTITIES OF WATER. CONSULT A PHYSICIAN.

C. HAZARDS INFORMATION**FIRE AND EXPLOSION**

FLASH POINT - 482°F AUTO IGNITION TEMPERATURE - NA

UNUSUAL FIRE AND EXPLOSION HAZARDS - DECOMPOSITION AND COMBUSTION PRODUCTS MAY BE TOXIC.

HEALTH

INHALATION - IRRITATION, SENSITIZATION AND DERMATITIS.

INGESTION - MAY CAUSE GASTROINTESTINAL DISTRESS OR IRRITATION.

SKIN - PROLONGED AND REPEATED CONTACT MAY CAUSE IRRITATION AND RESULT IN SENSITIZATION AND ALLERGIC REACTION.

EYES - VAPOR MAY CAUSE IRRITATION, REDNESS AND TEARING. LIQUID MAY CAUSE SEVERE IRRITATION WITH POSSIBLE IRREVERSIBLE INJURY.

UNUSUAL CHRONIC TOXICITY - NONE KNOWN.

PERMISSIBLE CONCENTRATION (AIR) - NOT KNOWN

D. PRECAUTIONS/PROCEDURES

VENTILATION - GOOD MECHANICAL VENTILATION AND LOCAL EXHAUST

NORMAL HANDLING - DO NOT GET IN EYES, ON SKIN OR CLOTHING. DO NOT BREATHE VAPORS. KEEP CONTAINERS CLOSED. USE WITH ADEQUATE VENTILATION. WASH THOROUGHLY AFTER HANDLING.

STORAGE - STORE IN A COOL, DRY AREA AWAY FROM HEAT, STRONG OXIDIZERS. PROTECT FROM DAMAGE

SPILL OR LEAK - ABSORB SPILL ON SAND, EARTH OR VERMICULITE.

CAREFULLY COLLECT INTO CLOSED CONTAINERS FOR DISPOSAL ACCORDING TO FEDERAL, STATE OR LOCAL REGULATIONS.

FIRE EXTINGUISHING PRECAUTIONS - WEAR FULL PROTECTIVE GEAR AND NIOSH/MSHA APPROVED SELF-CONTAINED BREATHING APPARATUS.
FIRE EXTINGUISHING AGENTS TO AVOID - SOLID STREAM OF SPLATTERING AND SPREAD HAZARD.

SPECIAL PRECAUTIONS/PROCEDURES - COOL CONTAINERS EXPOSED TO FLAME WITH WATER SPRAY.

E. PERSONAL PROTECTIVE EQUIPMENT

RESPIRATORY EQUIPMENT - ORGANIC CHEMICAL CARTRIDGE RESPIRATOR, IF NEEDED.

EYES - CHEMICAL SPLASH - PROOF GOGGLES.

HANDS, ARMS AND BODY - RUBBER OR POLYETHYLENE GLOVES AND FULL BODY COVERING CLOTHING.

OTHER CLOTHING AND EQUIPMENT - EYE WASH FOUNTAIN AND SAFETY SHOWER.

F. PHYSICAL DATA

DESCRIPTION - DIGLYCIDYL ETHER RESIN

BOILING POINT - >200°F

VAPOR DENSITY - NA

SOLUBILITY IN WATER - NONE

EVAPORATION RATE - NIL

SPECIFIC GRAVITY - 0.94

VAPOR PRESSURE - CA. 1 MM HG AT 180C

PH - NA

% VOLATILES (BY VOLUME) - NIL

G. REACTIVITY DATA

STABILITY - STABLE

INCOMPATIBLE MATERIALS - STRONG OXIDIZERS, ACIDS AND EPOXY CURING AGENTS.

HAZARDOUS DECOMPOSITION PRODUCTS - CO, CO₂, NOT AS A RESULT OF THERMAL DECOMPOSITION.

HAZARDOUS POLYMERIZATION - WILL NOT OCCUR.

H. INGREDIENTS (MIXTURES)

INGREDIENTS	PERCENTAGE	CAS#	TLV	PEL
EPOXY RESIN	>85	28064-14-4	NE	NE
Silicon Dioxide SiO ₂	<20	14808-60-7	0.1mg/M ₃	0.1mg/M ₃
Tio ₂	<10	13463-67-7	10 MG/CU.M.	

I. ENVIRONMENTAL

BIODEGRADABILITY - NOT KNOWN

WASTE DISPOSAL METHODS - DISPOSE OF IN APPROVED WASTE DISPOSAL FACILITIES IN ACCORDANCE WITH FEDERAL, STATE AND LOCAL REGULATIONS. INCINERATION IS THE PREFERRED METHOD OF DISPOSAL.

J. REFERENCES

PERMISSIBLE CONCENTRATION REFERENCES - ACGIH TWA, TLV, AND STEL

REGULATORY STANDARDS - TITLE 49 CFR SECTION 173.118, 172.101

GENERAL - NIOSH GUIDE TO CHEMICALS

K. TRANSPORTATION INFORMATION

Not regulated under current DOT, IMO or ICAO regulations.

L. ADDITIONAL INFORMATION

EMPTY CONTAINER HANDLING!

WARNING! EMPTIED CONTAINER RETAINS PRODUCT RESIDUE AND VAPORS.
 OBSERVE ALL LABEL PRECAUTIONS EVEN AFTER CONTAINER IS EMPTIED.
 DO NOT CUT, DRILL, GRIND, OR WELD ON OR NEAR CONTAINER.

 INFORMATION CONTAINED HEREIN IS BELIEVED TO BE ACCURATE. HOWEVER, IT IS PROVIDED SOLELY FOR THE CUSTOMERS CONSIDERATION, INVESTIGATION AND VERIFICATION. PILGRIM PERMOCOAT, INC. HEREBY SPECIFICALLY DISCLAIMS ANY AND ALL WARRANTIES, EXPRESS OR IMPLIED, REGARDING THE ACCURACY AND COMPLETENESS OF SUCH INFORMATION, AND MAKES NO REPRESENTATIONS WITH RESPECT THERETO.

ENVIRONMENTAL DATA

SECTION I

PRODUCT/COMPOSITION

NO.	COMPONENT	CAS NUMBER	PERCENT
P	TITAN 501	NA	100
	EPOXY RESIN	28064-14-4	>85
	Silicon Dioxide SiO2	14808-60-7	<20
	Tio2	13463-67-7	<10

SECTION II

SARA TITLE III INFORMATION

NO.	EHS RQ (LBS) (*1)	EHS TPQ (LBS) (*2)	SEC 313 (*3)	313 CATEGORY (*4)	311/312 CATEGORIES (*5)
P					H-1

 FOOTNOTES-----

*1 = REPORTABLE QUANTITY OF EXTREMELY HAZARDOUS SUBSTANCE, SEC. 302

*2 = THRESHOLD PLANNING QUANTITY, EXTREMELY HAZARDOUS SUBSTANCE, SEC. 302

*3 = TOXIC CHEMICAL, SEC. 313

*4 = CATEGORY AS REQUIRED BY SEC. 313 (40 CFR 372.65 C), MUST BE USED ON TOXIC RELEASE INVENTORY FORM

*5 = HAZARD CATEGORY FOR SARA SEC. 313/312 REPORTING

HEALTH H-1 = IMMEDIATE (ACUTE) HEALTH HAZARD H-2 = DELAYED (CHRONIC) HEALTH HAZARD

PHYSICAL P-3 = FIRE HAZARD

P-4 = SUDDEN RELEASE OF PRESSURE HAZARD

P-5 = REACTIVE HAZARD

SECTION III

ENVIRONMENTAL RELEASE INFORMATION

KEEP OUT OF SURFACE WATERS, SEWERS, AND WATERWAYS ENTERING OR LEADING TO SURFACE WATERS. NOTIFY AUTHORITIES IF ANY EXPOSURE TO THE GENERAL PUBLIC OR ENVIRONMENT OCCURS OR IS LIKELY TO OCCUR.

SECTION IV**RCRA INFORMATION**

IF THIS PRODUCT BECOMES A WASTE, IT WOULD NOT BE A WASTE BY RCRA CRITERIA (40 CFR 261) PLACE IN AN APPROPRIATE DISPOSAL FACILITY IN COMPLIANCE WITH LOCAL REGULATIONS.